

## BulletCAT11 - LTE Advanced Carrier Aggregation 600Mbps CAT11 Gateway

The BulletCAT11 provides a feature packed, compact industrial strength wireless solution using robust LTE Advanced Carrier Aggregation technology for critical data communications. This Bullet provides incredibly fast CAT11 LTE connections with speeds of up to 600 Mbps for today's data intensive applications. The BulletCAT11 features Gigabit Ethernet, RS232/485 Serial Data, 2x Programmable I/O and GPS.

*CAT11 - 600 Mbps LTE*

*Carrier Aggregation*

*Quad Constellation GPS*

*Gigabit Ethernet*

*Industrial Temperature*

*RS232/485 Serial Port*



## Features

- Ultra Fast CAT 11 LTE Operation
- Up to 600 Mbps Downlink / 75 Mbps Uplink Over Air
- Increased performance with Carrier Aggregation
- Data Usage & Systems Alerts (Email, SMS)
- Firewall with ACL Security, DMZ & Port Forwarding
- 2x Programmable Analog/Digital Inputs or 2 Digital Outputs
- IPSec, GRE / VPN Tunneling
- RS232/485 Serial Console/Data Port
- 10/100/1000 Ethernet (PoE)
- IPv6 & IPv4 Support
- MQTT Support
- Quad Constellation GPS (TCP/UDP/SMTP)
- Wide Operating Temperature (-40°C to +85°C)
- User interface via SSH or HTTP/HTTPS web browser
- Microhard NMS Support



# BulletCAT11

# Specifications

<b>Supported Bands</b>	<b>LTE FDD LTE TDD HSPA+</b> Bands 1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 20, 25, 26, 28, 29, 30, 66, 38, 40, 41 1, 2, 4, 5, 8  <b>LTE 2DL carrier aggregation combinations</b> North America B2+B2, B2+B4, B2+B5, B2+B12, B2+B13, B2+B17, B2+B29, B2+B30, B4+B4, B4+B5, B4+B7, B4+B12, B4+B13, B4+B17, B4+B29, B4+B30, B5+B30, B12+B12, B12+B30, B25+B25, B25+B26, B25+B41, B26+B41, B29+B30, B41+B41  <b>LTE 3DL carrier aggregation combinations</b> North America B2+B2+B12/17, B2+B2+B13, B2+B2+B4, B2+B4+B5, B2+B4+B12, B2+B4+B13, B2+B4+B29, B2+B5+B30, B2+B12+B12, B2+B12+B30, B2+B29+B30, B4+B4+B5, B4+B4+B7, B4+B4+B12, B4+B4+B13, B4+B5+B30, B4+B12+B12, B4+B12+B30, B4+B29+B30, B25+B26+B41, B25+B41+B41, B26+B41+B41, B41+B41+B41	<b>Security</b> VPN, IPSec with IKE/ISAKMP; Multiple tunnel support (16); 3DES and up to 256-bit AES Encryption, Site to Site Tunneling, L2TP, GRE, Open VPN, SSH, HTTPS, RADIUS	
<b>Cellular Data Features*</b> <small>*Module Standalone Laboratory Performance</small>	LTE: Up to 600 Mbps DL w/3x CA DL, 256QAM DL Up to 75 Mbps UL w/UL 64 QAM HSPA+ Rel. 8: DL/UL up to 42/11,5 Mbps	<b>Firewall</b> NAT, NAT-T VPN tunneling, Port forwarding, VPN/GRE pass-through; Access control lists (IP/MAC filtering), Data origin / integrity Authentication, DMZ	
<b>Serial Interface</b>	RS232/485 Serial Data Port	<b>Management</b> Telnet, WebUI, SNMP V1/2/3, Wireless Upgrade (HTTP/FTP), RADIUS authentication, AT Command Interface (Serial/Telnet), Microhard NMS Support, Data Usage Alerts, SSH	
<b>Serial Baud Rate</b>	300bps to 921kbps	<b>Diagnostics</b> RSSI, Ec/No, Voltage, Temperature, Remote diagnostics, Watchdog, UDP Event Reporting, SMS Alerts, Netflow	
<b>Serial Port Server</b>	Extensive Serial Port Support: TCP Server/Client / UDP Server/Client / Modbus / SMTP	<b>Input Voltage</b> 7 - 30VDC or Passive PoE on LAN Reverse polarity protection	
<b>Ethernet</b>	10/100/1000 BaseT, Auto - MDI/X IEEE 802.3	<b>Connectors:</b> Antenna 3x SMA Female (Cell, Cell Div, GPS) Data RJ-45 (Ethernet) 4 PIN Interlock (Vin, I/O) DB9 RS232 USB Micro-AB SIM 1.8 / 3.0V	
<b>I/O</b>	2x Programmable Analog/Digital Inputs or 2x Digital Outputs	<b>Environmental</b> Operating Temperature -40°C to +85°C -40°F to +185°F Humidity 5-95%, non-condensing	
<b>USB</b>	USB 2.0 USB (Device)	<b>Weight</b> Approx. 150 grams	
<b>GPS</b>  GNSS Systems GLONASS, BeiDou & Galileo GPS Protocols NMEA 0183 V3.0 Acquisition Sensitivity -145 dBm (Cold-start) Tracking Sensitivity -160 dBm (Open Sky/Active-patch Antenna) Accuracy <2m CEP-50 (Open sky, 1 Hz tracking) Standalone time to first fix 1s/29s/32s (hot/warm/cold) Total number of SVs ~55 SVs	TCP/UDP/Email Reporting, GpsGate, TAIP	<b>Dimensions</b> Approx. 1.75" x 3.25" x 1.0" (45mm x 85mm x 25mm)	
<b>SMS</b>	SMS to/from Ethernet via Telnet SMS Alerts SMS Remote Reboots	<b>Approvals</b> FCC / IC PTCRB Carrier Specific Approvals	
<b>Carrier Connection</b>	ICMP Keep Alive, DDNS	<b>Order Options</b>	
<b>Network Protocols</b>	IPv4, IPv6, TCP, UDP, TCP/IP, ARP, ICMP, DHCP, HTTP, SNMP, FTP, DNS, Serial over IP, Modbus Slave (TCP/Serial), MQTT	<b>Model</b> BulletCAT11	

## Contact Information

Microhard Systems Inc.  
 150 Country Hills Landing N.W.  
 Calgary, AB, Canada T3K 5P3

Email: [info@microhardcorp.com](mailto:info@microhardcorp.com)  
 Tel: (403) 248-0028  
 Fax: (403) 248-2762

Copyright 2018 Microhard Systems Inc.  
 Specifications subject to change without notice.

