

BulletPlus - 4G/LTE Ethernet/Serial/USB Gateway w/WiFi

The all new BulletPlus-B provides a feature packed, compact industrial strength wireless solution using ultra fast 4G LTE technology for critical data applications. The BulletPlus features three 10/100 Ethernet Ports, Dual SIM support, 802.11b/g/n WiFi, RS232 Serial Data, 2x Programmable I/O and Standalone GPS.

4G LTE w/Fallback

Dual SIM

Standalone GPS

3x Ethernet Ports

Low Power

RS232 Serial Port



New Cell Module!

Features

- Low Power Consumption
- Ultra Fast 4G/LTE Operation
- Up to 150Mbps Downlink / 50 Mbps Uplink Over Air
- Dual SIM Card Support w/Failover
- Support for 802.11b/g/n devices (Up to 150 Mbps)
- IP Pass-through Mode
- Firewall with ACL Security, DMZ & Port Forwarding
- 2x Programmable Analog/Digital Inputs or 2 Digital Outputs
- IPSec, GRE / VPN Tunneling
- RS232 Serial Data/Console Port
- 3 - 10/100 Ethernet (PoE), (3x LAN or 1x WAN/2xLAN)
- USB Host Port
- Standalone GPS (TCP Server, UDP Reporting, SMTP)
- Wide Operating Temperature (-40°C to +85°C)
- Data Usage Alerts (Email, SMS)
- User interface via telnet or web browser
- Microhard NMS Support



BulletPlus

Specifications

Cellular Supported Bands	LTE FDD Bands: 1, 2, 3, 4, 5, 7, 8, 11, 12, 13, 17, 18, 19, 20, 21, 26, 28, 29, 30, 66 LTE TDD Bands: 38, 39, 40, 41 HSPA+ Bands: 1, 2, 4, 5, 8	Security	VPN, IPSec with IKE/ISAKMP; Multiple tunnel support (16); 3DES and up to 256-bit AES Encryption, VPN Tunneling L2TP, GRE, HTTPS, RADIUS																																				
Cellular Data Features*	LTE: DL 150 Mbps, UL 50 Mbps HSPA+: DL 42 Mbps, UL 5.7 Mbps WCDMA: DL/UL 384 kbps EDGE Class 33: DL/UL 236.8 kbps GPRS Class 33: DL/UL 85.6kbps	Firewall	NAT, NAT-T VPN tunneling, Port forwarding, VPN/GRE pass-through; Access control lists, DMZ																																				
<i>*Module Standalone Laboratory Performance</i>		Management	Telnet, WebUI, SNMP V1/2/3, Wireless Upgrade (HTTP/FTP), AT Command Interface (Serial/Telnet), Microhard NMS Support, Data Usage Alerts, SSH																																				
WiFi Features	802.11b/g/n (2.4GHz)	Diagnostics	RSSI, Ec/No, Voltage, Temperature, Remote diagnostics, UDP Event Reporting, SMS Alerts, Netflow																																				
WiFi Performance	<table border="1"> <thead> <tr> <th>Rate</th> <th>Mode</th> <th>Tx (dBm)</th> <th>Rx (dBm)</th> </tr> </thead> <tbody> <tr> <td>1 Mbps</td> <td>b</td> <td>30</td> <td>-97 ± 1</td> </tr> <tr> <td>11 Mbps</td> <td>b</td> <td>30</td> <td>-92 ± 1</td> </tr> <tr> <td>6 Mbps</td> <td>g</td> <td>30</td> <td>-94 ± 1</td> </tr> <tr> <td>54 Mbps</td> <td>g</td> <td>26</td> <td>-75 ± 1</td> </tr> <tr> <td>MCS0</td> <td>n (HT20)</td> <td>30</td> <td>-96 ± 1</td> </tr> <tr> <td>MCS7</td> <td>n (HT20)</td> <td>26</td> <td>-75 ± 1</td> </tr> <tr> <td>MCS0</td> <td>n (HT40)</td> <td>30</td> <td>-94 ± 1</td> </tr> <tr> <td>MCS7</td> <td>n (HT40)</td> <td>26</td> <td>-73 ± 1</td> </tr> </tbody> </table>	Rate	Mode	Tx (dBm)	Rx (dBm)	1 Mbps	b	30	-97 ± 1	11 Mbps	b	30	-92 ± 1	6 Mbps	g	30	-94 ± 1	54 Mbps	g	26	-75 ± 1	MCS0	n (HT20)	30	-96 ± 1	MCS7	n (HT20)	26	-75 ± 1	MCS0	n (HT40)	30	-94 ± 1	MCS7	n (HT40)	26	-73 ± 1	Input Voltage	7 - 30VDC Passive PoE on WAN (Optional) Reverse polarity protection
Rate	Mode	Tx (dBm)	Rx (dBm)																																				
1 Mbps	b	30	-97 ± 1																																				
11 Mbps	b	30	-92 ± 1																																				
6 Mbps	g	30	-94 ± 1																																				
54 Mbps	g	26	-75 ± 1																																				
MCS0	n (HT20)	30	-96 ± 1																																				
MCS7	n (HT20)	26	-75 ± 1																																				
MCS0	n (HT40)	30	-94 ± 1																																				
MCS7	n (HT40)	26	-73 ± 1																																				
Serial Interface	RS232 Serial Data Port	Current Consumption (@12VDC)	Idle (LTE Connected): 120 mA WiFi (AP mode+LTE): 170 mA																																				
Serial Baud Rate	300bps to 921kbps	Connectors:	<table border="0"> <tr> <td>Antenna</td> <td>3x SMA Female (Cell, Div, GPS)</td> </tr> <tr> <td></td> <td>1x RPSMA Female (WiFi)</td> </tr> <tr> <td>Data</td> <td>3x RJ-45 (Ethernet)</td> </tr> <tr> <td></td> <td>4 PIN Interlock (Vin, I/O)</td> </tr> <tr> <td></td> <td>DB9 RS232</td> </tr> <tr> <td>USB</td> <td>Type A</td> </tr> <tr> <td>SIM</td> <td>2x 1.8 / 3.0V (2FF)</td> </tr> </table>	Antenna	3x SMA Female (Cell, Div, GPS)		1x RPSMA Female (WiFi)	Data	3x RJ-45 (Ethernet)		4 PIN Interlock (Vin, I/O)		DB9 RS232	USB	Type A	SIM	2x 1.8 / 3.0V (2FF)																						
Antenna	3x SMA Female (Cell, Div, GPS)																																						
	1x RPSMA Female (WiFi)																																						
Data	3x RJ-45 (Ethernet)																																						
	4 PIN Interlock (Vin, I/O)																																						
	DB9 RS232																																						
USB	Type A																																						
SIM	2x 1.8 / 3.0V (2FF)																																						
Serial Port Service	Extensive Serial Port Support: TCP Server/Client / UDP Server/Client / Modbus / SMTTP	Environmental	<table border="0"> <tr> <td>Operating Temperature</td> <td>-40°C to +85°C</td> </tr> <tr> <td>Humidity</td> <td>5-95%, non-condensing</td> </tr> <tr> <td>Vibration</td> <td>MIL-STD-810G</td> </tr> </table>	Operating Temperature	-40°C to +85°C	Humidity	5-95%, non-condensing	Vibration	MIL-STD-810G																														
Operating Temperature	-40°C to +85°C																																						
Humidity	5-95%, non-condensing																																						
Vibration	MIL-STD-810G																																						
Ethernet	2x LAN 10/100, Auto - MDI/X IEEE 802.3 1x WAN 10/100, Auto - MDI/X IEEE 802.3	Weight	Approx. 175 grams																																				
I/O	2x Programmable Analog/Digital Inputs or 2x Digital Outputs	Dimensions	Approx. 3.05" x 2.2" x 1.1" (77mm x 55mm x 28mm)																																				
USB	Host Type A USB 2.0	Approvals	FCC / IC UL HazLoc PTCRB Carrier Specific Approvals																																				
GPS	TCP Server, UDP/Email Reporting, GpsGate GPS, GNSS, GLONASS, BeiDou	Order Options																																					
Navigation Update Rate Accuracy	Up to 5 Hz	MHS117501	BulletPlus-B																																				
Position:	2.5 m CEP																																						
SBAS:	2.0 m CEP																																						
Tracking :	-160 dBm																																						
Cold Starts:	-145 dBm																																						
Hot Starts:	-155 dBm																																						
	*Sensitivities are typical and may vary																																						
SMS	SMS to/from Ethernet via Telnet SMS Alerts SMS Remote Control																																						
Carrier Connection	PAP, CHAP, ICMP Keep Alive, Traffic Watchdog, DDNS, IP pass-through.																																						
Network Protocols	TCP, UDP, TCP/IP, ARP, ICMP, DHCP, HTTP, SNMP, FTP, DNS, Serial over IP, Modbus Slave (TCP/Serial)																																						

Contact Information

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762

Copyright 2018 Microhard Systems Inc.
Specifications subject to change without notice.

