

900MHz Ethernet/Serial/USB Gateway

The IP920B 900MHz Wireless Ethernet/Serial/USB Gateway is powered by a reliable and high speed 900 MHz FHSS radio. It provides robust wireless communication of simultaneous RS232/485 Serial , USB and IP/ Ethernet data, resulting in a powerful solution to fit the needs of any wireless application.

Up to 345 kbps

Up to 1 Watt

Low Latency

Extended Temperature

USB 2.0

RS232/485/422 Port



Features

- Up to 345 kbps wireless link rate
- Long range, high speed communications with excellent receiver sensitivity and robust frequency hopping
- Two serial ports: RS232 and RS232/485/422
- Master, Remote, and Repeater Modes
- Supports Point-to-Point, Point-to-Multipoint, Repeater, Peer-to-Peer
- Adjustable transmit power (100mW - 1W)
- Bringing industrial data into IP/Ethernet networks
- Radius Server Authentication
- Full VLAN Support
- User interface through local console, telnet, and web browser
- Network management capability with SNMP V1, V2, V3
- Local and remote firmware upgrading through FTP



IP920B

Specifications

| | | | |
|--------------------------|--|----------------------|---|
| Frequency | 902 - 928 MHz | Input Voltage | 9-30VDC |
| Spread Method | Frequency Hopping | Connectors | Antenna Data RP-TNC Female Bulkhead 2 - RS232 DB-9F Locking screw connector RJ-45 (Ethernet) Mini-USB |
| Link Rate | 275kbps or 345Mbps (User-Select) | | |
| Error Detection | 32 bits of CRC, ARQ | Environmental | -40°F to 185°F (-40°C to +85°C) 5-95% humidity, noncondensing |
| Encryption | 128-bit WEP/WPA (Canada & USA only. NOT AVAILABLE for export, see -AES option) | Weight | Approx. 0.92lbs (420g) |
| Range | 60+ miles (100+ km) @ 345kbps link rate, line of sight) | Dimensions | Approx. 4.755" x 3.75" x 1.75" (121mm x 95.3mm x 44.5mm) |
| Sensitivity | -106dBm @ 345kbps link rate | Enclosure | Extruded Aluminum |
| Output Power | 100mW - 1W (20-30dBm) | Mount | Panel Mount |
| System Gain | 140dB w/Rubber Ducky antennas | Approvals | FCC Part 15.247 IC RSS210 |
| Serial Interface | RS232: RxD, TxD, RTS, CTS, DCD, DSR, DTR RS422: Tx+, Tx-, Rx+, Rx- RS485: 4-wire/2-wire | Order Options | |
| Serial Baud Rate | 300bps to 921kbps | -DIN | DIN rail mount kit |
| USB | USB 2.0 USB Console Port USB to Serial Data Routing USB to Ethernet Data Routing | -C1D2 | Class 1 Div 2 (for use in hazardous environments) |
| Ethernet | 10/100 BaseT IEEE 802.3 | -AES | 128/256-bit AES Encryption, Secure Shell, HTTPS (Canada & USA only. NOT AVAILABLE for export) |
| Network Protocols | TCP, UDP, TCP/IP, ARP, ICMP, DHCP, HTTP, SNMP, FTP, Serial over IP, QoS | -AU | Australian Hop Tables (915 to 928 MHz) |
| Management | Local Serial Port Console, Telnet, WebUI, SNMP, FTP Upgrade, RADIUS authentication, VLAN | -NZ | New Zealand Hop Tables (921 to 929 MHz) |
| Operating Modes | Point-to-Point, Point-to-Multipoint, Store & Forward Repeater, Peer-to-Peer | | |
| Diagnostics | VSWR, Battery Voltage, Temperature, RSSI, and remote diagnostics | | |
| Rejection | Excellent strong signal interference & rejection characteristics | | |

Contact Information

Copyright 2015 Microhard Systems Inc.
Specifications subject to change without notice.

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762

