

# Nano IP Series IPn2420



## Miniature OEM Wireless Ethernet/Serial/USB Gateway

The Nano IP Series adds Ethernet capability to the miniature, yet powerful Nano platform. This incredibly small Ethernet Bridge and Serial Gateway provides robust wireless communication of simultaneous serial data and IP/Ethernet packets to extend serial data and IP networks.

*Microhard Systems Inc.'s proprietary radio technology excels in the most demanding RF and physical environments.*

The Nano IP platform is the smallest form factor (2" x 1.25" x .5", weighing only 25 grams) available which offers a full Ethernet/Serial/USB bridge and routing functionality. The Nano IP OEM module can be directly integrated into OEM systems or applications using a variety of interface options. With the LAN out interface ready to wire directly to CAT5 cable OEMs can integrate this unit quickly and efficiently. The Nano IP Series also features flexible maintenance utilities, secure firewall features and network management facilities. Robust Frequency Hopping with excellent receiver sensitivity and interference rejection allow for long range, high speed communications.



**Weighs only 25grams!**

**2" X 1.25" X 0.5"**

**World's Smallest Ethernet//Serial/USB Gateway!**

### Features of the IPn2420

- Low Power Consumption
- Up to 1.2 Mbps Wireless Link Rate\*
- Multicast Support
- Master, Slave, Repeater operation in a single unit
- HV Option provides a quick wiring solution with Ethernet and Serial Levels and Power (7-30 VDC)
- 2 Serial Com Ports, 1 USB Port, and 1 Ethernet Port
- Supports Point-to-Point, Point-to-Multipoint, Repeater, Peer-to-Peer
- Adjustable transmit power (100mW - 1W)
- Radius Server Support
- Full VLAN Support (for separate management and Data networking)
- User interface through local console, telnet, and web browser
- Network management capability with SNMP V1, V2, V3
- Local and remote wireless firmware upgrading through FTP
- QoS Routing on Serial, IP, or Logic Ports

### Interface Options

#### Enclosed Solution



#### Motherboard Solution

\* For Faster Link Rates Contact Microhard

◆ VLAN ◆ RADIUS ◆ QoS ◆ HTTPS ◆ USB ◆ Firewall

# IPn2420

# Specifications

<b>Frequency</b>	2.4000 - 2.4835 GHz	<b>Input Voltage</b>	OEM Enclosed Interface Card	3.3VDC Nominal (+/- 0.3V) 7-30VDC 7-30VDC
<b>Spread Method</b>	Frequency Hopping / DTS	<b>Connectors:</b>	<b>OEM</b> Antenna Data <b>Enclosed</b> Antenna Data	OEM - MMCX OEM - 60 Pin OEM Header x2 RPSMA Female Bulkhead RJ-45 (Ethernet) Female DB9 Mini-USB
<b>Link Rate</b>	Up to 1.2Mbps (See Order Options)			
<b>Error Detection</b>	32 bits of CRC, ARQ			
<b>Encryption</b>	128-bit WEP/WPA (Canada & USA only. NOT AVAILABLE for export, see -AES option)			
<b>Range</b>	Up to 15+ miles (25+ km) @ 1.2Mbps Up to 30+ miles (50+ km) @ 172kbps			
<b>Sensitivity</b>	-107 @ 172kbps link rate -97 @ 1.2Mbps link rate	<b>Environmental</b>	Temperature Humidity	-40°F to 185°F (-40°C to +85°C) 5-95%, non-condensing
<b>Output Power</b>	100mW - 1W (20-30dBm)	<b>Weight (Including Radio)</b>	OEM Enclosed w/ Interface Board	Approx. 25 grams Approx. 250 grams Approx. 70 grams
<b>Serial Interface</b>	RS232, RS485, RS422	<b>Dimensions</b>	OEM Enclosed	Approx. 1.25" x 2.0" x .50" (32mm x 51mm x 13mm) Approx. 2.25" x 3.85" x 1.50" (57mm x 98mm x 38mm)
<b>Serial Baud Rate</b>	300bps to 921kbps			
<b>USB</b>	USB 2.0 USB Console Port USB to Serial Data Routing USB to Ethernet Data Routing	<b>Approvals</b>	FCC Part 15.247 IC RSS210	
<b>Ethernet</b>	10/100 BaseT, Auto - MDI/X IEEE 802.3	<b>Order Options</b>		
<b>Network Protocols</b>	TCP, UDP, TCP/IP, TFTP, ARP, ICMP, DHCP, HTTP, HTTPS*, SSH*, SNMP, FTP, DNS, Serial over IP, QoS (* Only available in -AES)	<b>-C1D2</b>	Class 1 Div 2 (for use in hazardous environments)	
<b>Operating Modes</b>	Point-to-Point, Point-to-Multipoint, Store & Forward Repeater, Peer-to-Peer	<b>-AES</b>	128/256-bit AES Encryption, Secure Shell, HTTPS (Canada & USA only. NOT AVAILABLE for export)	
<b>Management</b>	Local Serial Port Console, Telnet, WebUI, SNMP, FTP & Wireless Upgrade, RADIUS authentication, VLAN	<b>-EXP</b>	Export Version, removes encryption	
<b>Diagnostics</b>	Battery Voltage, Temperature, RSSI, and remote diagnostics	<b>IPn2420F</b> <b>IPn2420T</b>	115kbps - 230kbps 1.2Mbps	
<b>Rejection</b>	Excellent strong signal interference & rejec- tion characteristics			
<b>Input IP3</b> (Antenna Connector)	+12 dBm			

## Contact Information

Copyright 2015 Microhard Systems Inc.  
Specifications subject to change without notice.

Microhard Systems Inc.  
150 Country Hills Landing N.W.  
Calgary, AB, Canada T3K 5P3

Email: [info@microhardcorp.com](mailto:info@microhardcorp.com)  
Tel: (403) 248-0028  
Fax: (403) 248-2762



[www.microhardcorp.com](http://www.microhardcorp.com)