

Nano IP Series IPn2420



Miniature OEM Wireless Ethernet/Serial/USB Gateway

The Nano IP Series adds Ethernet capability to the miniature, yet powerful Nano platform. This incredibly small Ethernet Bridge and Serial Gateway provides robust wireless communication of simultaneous serial data and IP/Ethernet packets to extend serial data and IP networks.

Microhard Systems Inc.'s proprietary radio technology excels in the most demanding RF and physical environments.

The Nano IP platform is the smallest form factor (2" x 1.25" x .5", weighing only 25 grams) available which offers a full Ethernet/Serial/USB bridge and routing functionality. The Nano IP OEM module can be directly integrated into OEM systems or applications using a variety of interface options. With the LAN out interface ready to wire directly to CAT5 cable OEMs can integrate this unit quickly and efficiently. The Nano IP Series also features flexible maintenance utilities, secure firewall features and network management facilities. Robust Frequency Hopping with excellent receiver sensitivity and interference rejection allow for long range, high speed communications.



Weighs only 25grams!

2" X 1.25" X 0.5"

World's Smallest Ethernet//Serial/USB Gateway!

Features of the IPn2420

- Low Power Consumption
- Up to 1.2 Mbps Wireless Link Rate*
- Multicast Support
- Master, Slave, Repeater operation in a single unit
- HV Option provides a quick wiring solution with Ethernet and Serial Levels and Power (7-30 VDC)
- 2 Serial Com Ports, 1 USB Port, and 1 Ethernet Port
- Supports Point-to-Point, Point-to-Multipoint, Repeater, Peer-to-Peer
- Adjustable transmit power (100mW - 1W)
- Radius Server Support
- Full VLAN Support (for separate management and Data networking)
- User interface through local console, telnet, and web browser
- Network management capability with SNMP V1, V2, V3
- Local and remote wireless firmware upgrading through FTP
- QoS Routing on Serial, IP, or Logic Ports

Interface Options

Enclosed Solution



Motherboard Solution

* For Faster Link Rates Contact Microhard

◆ VLAN ◆ RADIUS ◆ QoS ◆ HTTPS ◆ USB ◆ Firewall

IPn2420

Specifications

Frequency	2.4000 - 2.4835 GHz	Input Voltage	OEM Enclosed Interface Card	3.3VDC Nominal (+/- 0.3V) 7-30VDC 7-30VDC
Spread Method	Frequency Hopping / DTS	Connectors:	OEM Antenna Data Enclosed Antenna Data	OEM - MMCX OEM - 60 Pin OEM Header x2 RPSMA Female Bulkhead RJ-45 (Ethernet) Female DB9 Mini-USB
Link Rate	Up to 1.2Mbps (See Order Options)			
Error Detection	32 bits of CRC, ARQ			
Encryption	128-bit WEP/WPA (Canada & USA only. NOT AVAILABLE for export, see -AES option)			
Range	Up to 15+ miles (25+ km) @ 1.2Mbps Up to 30+ miles (50+ km) @ 172kbps			
Sensitivity	-107 @ 172kbps link rate -97 @ 1.2Mbps link rate	Environmental	Temperature Humidity	-40°F to 185°F (-40°C to +85°C) 5-95%, non-condensing
Output Power	100mW - 1W (20-30dBm)	Weight (Including Radio)	OEM Enclosed w/ Interface Board	Approx. 25 grams Approx. 250 grams Approx. 70 grams
Serial Interface	RS232, RS485, RS422	Dimensions	OEM Enclosed	Approx. 1.25" x 2.0" x .50" (32mm x 51mm x 13mm) Approx. 2.25" x 3.85" x 1.50" (57mm x 98mm x 38mm)
Serial Baud Rate	300bps to 921kbps			
USB	USB 2.0 USB Console Port USB to Serial Data Routing USB to Ethernet Data Routing	Approvals		FCC Part 15.247 IC RSS210
Ethernet	10/100 BaseT, Auto - MDI/X IEEE 802.3	Order Options		
Network Protocols	TCP, UDP, TCP/IP, TFTP, ARP, ICMP, DHCP, HTTP, HTTPS*, SSH*, SNMP, FTP, DNS, Serial over IP, QoS (* Only available in -AES)	-C1D2		Class 1 Div 2 (for use in hazardous environments)
Operating Modes	Point-to-Point, Point-to-Multipoint, Store & Forward Repeater, Peer-to-Peer	-AES		128/256-bit AES Encryption, Secure Shell, HTTPS (Canada & USA only. NOT AVAILABLE for export)
Management	Local Serial Port Console, Telnet, WebUI, SNMP, FTP & Wireless Upgrade, RADIUS authentication, VLAN	-EXP		Export Version, removes encryption
Diagnostics	Battery Voltage, Temperature, RSSI, and remote diagnostics	IPn2420F IPn2420T		115kbps - 230kbps 1.2Mbps
Rejection	Excellent strong signal interference & rejec- tion characteristics			
Input IP3 (Antenna Connector)	+12 dBm			

Contact Information

Copyright 2015 Microhard Systems Inc.
Specifications subject to change without notice.

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762



www.microhardcorp.com