

2.4 GHz Spread Spectrum Wireless Modem

The Spectra 2420 is a 2.4 GHz Frequency Hopping Wireless Modem, operating in the 2.4000 - 2.4835 GHz ISM band. The Spectra 2420 offers robust, low latency wireless, which can be optimized for long distance communications of over 30 miles (50km). The fully supported serial ports offer RS232/RS485/RS422 interfaces for any type of serial based device!

Up to 230 kbps

100mW to 1W

Enhanced Range

Extended Temperature

RSSI Indicators

RS232/485/422



Features

- **Transparent, low latency link, providing up to 230 kbps continuous throughput to support protocols such as MODBUS**
- **RS232/485/422 serial port communicates with virtually all types of PLCs, RTUs, and other serial devices**
- **Extended temperature specification (-40 to +85°C)**
- **Supports Point-to-Point, Point-to-Multipoint, Peer-to-Peer, Store and Forward Repeater, TDMA, Multimaster**
- **Adjustable transmit power (100mW - 1W)**
- **Low power consumption in Sleep Mode**
- **32 bits of CRC, selectable Forward Error Correction with retransmission**
- **Separate diagnostics port - transparent remote diagnostics and online network control**
- **RSSI LED's provide fast antenna alignment support**



Spectra 2420

Specifications

Frequency	2.4000 - 2.4835 GHz	Connectors	Antenna Data	RP-TNC Female Bulkhead Female DE9 Locking screw connector RJ-45
Spread Method	Frequency Hopping			
Band Segments	Selectable via Freq. Restriction	Environmental	Diagnostic	-40°F to 185°F (-40°C to +85°C) 5-95% humidity, noncondensing
Error Detection	32 bits of CRC, ARQ			
Encryption	Optional (see -AES option)	Weight		Approx. 0.92lbs (420g)
Range	30+ miles (50+ km) (dependant on link rate and line of sight)	Dimensions		Approx. 4.40" x 3.85" x 1.70" (111mm x 98mm x 43mm)
Sensitivity	-108dBm @ 172kbps link rate -116dBm @ 19.2kbps link rate (see -SL option)	Enclosure		Extruded Aluminum
Output Power	100mW - 1W (20-30dBm)	Mount		Panel Mount
System Gain	142dB w/Rubber Ducky antennas	Approvals		FCC Part 15.247 IC RSS210
Serial Interface	RS-232/RS485/RS422	Order Options		
Serial Baud Rate	300bps to 230.4kbps	-DIN		DIN rail mount kit
Link Rate	19.2 kbps - 230.4kbps (See Order Options)	-FT		Standard FAST Mode 115kbps - 230.4kbps
Operating Modes	Point-to-Point, Point-to-Multipoint, Store & Forward Repeater, Peer-to-Peer, TDMA, Multimaster	-SL		Extended sensitivity / SLOW Mode 19.2kbps - 230.4kbps
Signals Interface	RxD1, TxD1, RTS, CTS, DCD, DSR, DTR, RxD2, TxD2, RSSI LEDs, Tx/Rx LEDs, Reset, Config, Wake-up, RSmode	-C1D2		Class 1 Div 2 (for use in hazardous environments)
Diagnostics	Battery Voltage, Temperature, RSSI, and remote diagnostics	-AES		128-AES Encryption (Requires export permit outside Canada & USA)
Rejection	Excellent strong signal interference & rejection characteristics			
Input Voltage	9-30VDC			

Contact Information

Copyright 2012 Microhard Systems Inc.
Specifications subject to change without notice.

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762

