


Low Size, Weight, Power & Cost Enclosed Digital Data Link

The pMDDL2550-SWP Digital Data Link is a compact enclosed, high power, 2x2 MIMO 2.5GHz wireless solution that provides the bandwidth and range needed for complex data intensive applications. The pMDDL2550-SWP features 2x2 MIMO Digital Data Link, using Maximal Ratio Combining (MRC), Maximal Likelihood (ML) decoding and Low-Density Parity Check (LDPC) to achieve robust RF performance. The pMDDL2550-SWP features secure & simultaneous Ethernet and Serial Data communications.

Only 37 grams!



36 x 48 x 15 mm

Low Cost

> 50 km Range

Up to 25 Mbps

34 dBm (2.5W)

Ethernet & Serial

PTP | PMP | Relay | MESH

Features

- Robust 2X2 MIMO 2.5GHz Operation
- Adjustable total transmit power (up to 34dBm)
- Maximal Ratio Combining (MRC), Maximal Likelihood (ML) decoding
- Low-Density Parity Check (LDPC)
- Up to 25Mbps Iperf Throughput @ 8MHz channel (-78dBm)
 - Up to 2Mbps IPerf Throughput @ 4MHz channel (-102dBm)
- Small foot print and lightweight
- Serial Communication Port
- Dual 10/100 Ethernet Ports (LAN/WAN)
- Supports Point-to-Point, Point-to-Multipoint and Mesh Networks
- Master, Remote, Relay, Mesh Operating Modes.
- Interface through local console, telnet, and web browser
- Local and remote wireless firmware upgrading through FTP



**SWP Expander Board
& Interface Cable**

pMDDL2550-SWP Specifications



Frequency	2.500 - 2.570GHz
Error Detection	32 bits of CRC, ARQ
Encryption (Requires Export Permit)	128-bit AES (Optional 256-bit AES)
Ports	Serial Data/Console Ethernet USB
	RS232 (300bps - 230kbps) Dual 10/100BaseT IEEE802.3 (LAN/WAN) 2.0
Firewall	Port Forwarding, Access Control, IP/MAC List
Operating Modes	Point-to-Point, Point-to-Multipoint, Relay, Mesh
Diagnostics	Remote Diagnostics, Ping, Traceroute, ARP table, DHCP active leases, IPPerf, RSSI
Management	Local Serial Port Console, Telnet, WebUI, SNMP, FTP Upgrade, TFTP, CLI (Command Line Interface)
Rejection	Excellent strong signal interference & rejection characteristics
Input Voltage	8 - 30 V _{DC}
Mating Connector	Power, Data: 10-Pin (GHR-10V-S) Antenna(s): 2x MMCX
Environmental	Temperature Humidity
	-40°F to 185°F (-40°C to +85°C) 5-95%, non-condensing
Weight	~37 grams
Dimensions	~36 x 48 x 15 mm

Order Options

MHK185770	SWP 2X2 MIMO 2.5 GHz Digital Data Link
------------------	----------------------------------------

Optimal Performance Specifications			
Modulation	IPerf Throughput (Mbps)	Optimal MRC Sensitivity (dBm)	Total Tx Power (dBm) +/- 1dB
8 MHz (2X2 MIMO ON)			
BPSK_1/2	3	-99.5	34dBm
QPSK_1/2	5.9	-98	34dBm
QPSK_3/4	8.8	-96	34dBm
16QAM_1/2	11.6	-92	34dBm
16QAM_3/4	17.1	-90	31dBm
64QAM_2/3	22.8	-85	30dBm
64QAM_3/4	25.5	-83.5	30dBm
64QAM_5/6	27.8	-81	30dBm
4 MHz (2X2 MIMO ON)			
BPSK_1/2	1.51	-102.5	34dBm
QPSK_1/2	2.98	-101	34dBm
QPSK_3/4	4.4	-99	34dBm
16QAM_1/2	5.8	-95.5	34dBm
16QAM_3/4	8.6	-93	31dBm
64QAM_2/3	11.4	-88	30dBm
64QAM_3/4	12.8	-86	30dBm
64QAM_5/6	14	-83.5	30dBm

Modulation	IPerf Throughput (Mbps)	Optimal MRC Sensitivity (dBm)	Total Tx Power (dBm) +/- 1dB
8 MHz (MIMO OFF)			
BPSK_1/2	3	-96.5	31dBm
QPSK_1/2	5.8	-95	31dBm
QPSK_3/4	8.6	-93	31dBm
16QAM_1/2	11.5	-89	31dBm
16QAM_3/4	16.9	-87	30dBm
64QAM_2/3	22.2	-82	28dBm
64QAM_3/4	24.7	-80.5	28dBm
64QAM_5/6	27.4	-78	27dBm
4 MHz (MIMO OFF)			
BPSK_1/2	1.5	-99.5	31dBm
QPSK_1/2	2.9	-98	31dBm
QPSK_3/4	4.3	-96	31dBm
16QAM_1/2	5.7	-92.5	31dBm
16QAM_3/4	8.4	-90	30dBm
64QAM_2/3	11.3	-85	28dBm
64QAM_3/4	12.5	-83	28dBm
64QAM_5/6	14	-80.5	27dBm

Microhard Confidential

Preliminary



Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

www.microhardcorp.com
info@microhardcorp.com
1-855-353-0028