

High Performance 5G Cellular Dual Ethernet/Serial Gateway w/ Dual SIM

The IPn5G is a high performance, industrial strength, multi-network router for fixed and mobile applications. The IPn5G rugged 5G router/gateway features a Qualcomm Snapdragon Chipset and is capable of up to 3.4 Gbps download¹ and 900 Mbps upload¹, ideal for data hungry applications! The IPn5G features Dual Gigabit Ethernet, Dual SIM w/Failover, 3x Serial Data Ports, 8x Programmable I/O and Integrated GPS.

5G



5G Cellular

Dual Gigabit Ethernet

8x Programmable I/O

Dual SIM w/Failover

3x Serial Data Ports

Features

- Ultra Fast 5G Operation with 4G/LTE Fallback
- Up to 3.4 Gbps Download / 900 Mbps Upload ¹
- Dual SIM Card Support w/Failover & Load Balancing
- Optional eSIM Support
- Firewall with ACL Security, DMZ & Port Forwarding
- Digital I/O - 8 Analog Inputs/Outputs or 8 Digital Outputs
- IPSec, GRE / VPN Tunneling
- 2 x Serial Data/Console Ports (RS232), 1 Data Port (RS485)
- 2 x 10/100/1000 Ethernet Ports (WAN/LAN)
- Multi WAN Failover
- USB 2.0 Port
- Integrated GPS (TCP/UDP/SMTP)
- Wide Operating Temperature (-40°C to +85°C)
- Data Usage Alerts (Email, SMS)
- User interface via SSH or HTTP/HTTPS web browser
- Microhard NMS2 & Microhard IoT Portal Support



IPn5G Specifications



Cellular Data Rate (Max.)¹

5G SA Sub-6	DL 2.4 Gbps; UL 900 Mbps
5G NSA Sub-6	DL 3.4 Gbps; UL 550 Mbps
LTE CAT19	DL 1.6 Gbps; UL 200 Mbps
WCDMA	DL 42 Mbps; UL 5.76 Mbps

Cellular Frequency Bands

5G NR	NSA	n1/ 2/ 3/ 5/ 7/ 8/ 12/ 13/ 14/ 18/ 20/ 25/ 26/ 28/ 29/ 30/ 38/ 40/ 41/ 48/ 66/ 70/ 71/ 75/ 76/ 77/ 78/ 79
	SA	n1/ 2/ 3/ 5/ 7/ 8/ 12/ 13/ 14/ 18/ 20/ 25/ 26/ 28/ 29/ 30/ 38/ 40/ 41/ 48/ 66/ 70/ 71/ 75/ 76/ 77/ 78/ 79
LTE	FDD	B1/ 2/ 3/ 4/ 5/ 7/ 8/ 12/ 13/ 14/ 17/ 18/ 19/ 20/ 25/ 26/ 28/ 29/ 30/ 32/ 66/ 71
	TDD	B34/ 38/ 39/ 40/ 41/ 42/ 43/ 48
	LAA	B46
UMTS	WCDMA	B1/ 2/ 4/ 5/ 8/ 19

Network

Carrier Connection	ICMP Keep Alive, Traffic Watchdog, DDNS, Failover
Network Protocols	IPv4, IPv6, TCP, UDP, TCP/IP, ARP, ICMP, DHCP, HTTP, SNMP, FTP, DNS, Serial over IP, Modbus Slave (TCP/Serial), Load Balancer
Security	VPN, IPsec with IKE/ISAKMP; Multiple tunnel support (16); 3DES and up to 256-bit AES Encryption, VPN Tunneling L2TP, GRE, Open VPN, HTTPS, RADIUS
Management	Telnet, WebUI, SNMP V1/2/3, Wireless Upgrade (HTTP/FTP), AT Command Interface (Serial/Telnet), Microhard NMS2 & IoT Portal Support, Data Usage Alerts, SSH
Diagnostics	RSSI, Ec/No, Voltage, Temperature, Remote diagnostics, UDP Event Reporting, SMS Alerts, Netflow

Serial

Serial Interface	1 x RS232 Data (Full Support) 1 x RS232 Console/Data (TX/RX) 1 x RS485 Data (2/4 wire) Baud Rate: 300bps to 921kbps TCP Server/Client / UDP Server/Client / Modbus / SMTP
-------------------------	---

Ethernet

LAN	2x RJ45 Ethernet Ports (10/100/1000 Gbps)
------------	---

I/O

8x Analog Input/Output or 8x Digital Outputs

USB

USB 2.0

GPS

Reporting	TCP/UDP/Email, GpsGate, TAIP
GNSS	GPS, GLONASS, BDS, Galileo, QZSS
GPS Protocols	NMEA 0183 V3.0
Acquisition Sensitivity	-145 dBm (Cold-start)
Tracking Sensitivity	-160 dBm (Open Sky/Active-patch Antenna)
Accuracy	<2m CEP-50 (Open sky, 1 Hz tracking)
Standalone time to first fix	1s/29s/32s (hot/warm/cold)
Total number of SVs	~55 SVs

Interfaces

Antenna	4x SMA Female (Main, DIV, MIMO1/2)
Data	2x RJ-45 (Ethernet)
	6 PIN Interlock (RS485)
	10 PIN Interlock (RS232/Digital I/O)
	DE9 RS232
	Micro USB
SIM	2x Nano (4FF), eSIM (Optional)
Power, I/O	4 PIN Interlock

Input Voltage

9 - 30V_{DC}
Reverse Polarity Protection

Environmental

Operating Temperature	-40°C to +85°C
Humidity	5-95%, non-condensing

Dimensions

Size	~57 mm (W) x 98 mm (L) x 45 mm (H)
Weight	~ 225 grams

Approvals

Regulatory	FCC, IC/ISED, PTCRB
Carrier	Carrier Specific Approvals
UL Hazloc (C1Div2)	Pending

Order Options

Model IPn5G

1. Chipset rated speeds



Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

www.microhardcorp.com
 info@microhardcorp.com
 1-855-353-0028