

LTECube-CAT4GL 150 Mbps CAT4 LTE IoT Ethernet Gateway

The LTECube-CAT4GL was engineered for the small size, low cost, and power requirements of the IoT & M2M applications that are growing across the globe. The LTECube-CAT4GL provides robust and reliable 150 Mbps CAT4 LTE connections. The LTECube-CAT4GL features Ethernet, USB, and powerful VPN/GRE Tunneling Capabilities.

CAT4 - 150 Mbps LTE

Compact Design

Low Cost!

Gigabit Ethernet

IPv6 & IPv4 Support

USB 2.0 Port



Features

- Fast & Robust CAT4 LTE Operation
- Engineered for IoT Applications
- Low Cost & Low Power Consumption
- Up to 150 Mbps Downlink / 50 Mbps Uplink Over Air
- Data Usage & Systems Alerts (Email, SMS)
- 1x Programmable Analog/Digital Input or 1x Digital Output*
- Firewall with ACL Security, DMZ & Port Forwarding
- IPSec(IKEv1/IKEv2), GRE / VPN, OpenVPN
- 10/100/1000 Ethernet w/PoE
- Full IPv6 & IPv4 Support
- MQTT Support
- LWM2M Support
- Wide Operating Temperature (-40°C to +85°C)
- User interface via SSH or HTTP/HTTPS web browser
- Microhard NMS Support

Only 1.75" x 1.75" x 1.35"!



LTECube-CAT4GL Specifications

Supported Bands	LTE FDD: B1,B2,B3,B4,B5,B7,B8,B12,B13, B18,B19,B20,B26,B28 TDD: B38,B39,B40,B41 WCDMA: B1,B2,B4,B5,B8,B6,B19 GSM: B2/B3/B5/B8	Diagnostics	RSSI, Ec/No, Temperature, Remote diagnostics, Watchdog, UDP Event Reporting, SMS Alerts, Netflow
Cellular Data Features*	LTE FDD: Up to 150 Mbps DL, 50 Mbps UL LTE TDD: Up to 130 Mbps DL, 35 Mbps UL DC-HSPA+: Up to 42 Mbps DL, 5.7 Mbps UL WCDMA: Up to 384 Kbps DL, 384 Kbps UL EDGE: Up to 296 Kbps DL, 236.8 Kbps UL GSM: Up to 107 Kbps DL, 85.6 Kbps UL	Input Voltage	7 - 30VDC PoE (Passive, Max 24V)
Module Standalone Laboratory Performance		I/O	1x Programmable Analog/Digital Input or 1x Digital Output *Only on devices built Nov 2022 onwards
Ethernet	10/100/1000, Auto - MDI/X IEEE 802.3	Connectors:	Antenna 3x SMA Female (Main, Diversity, GPS) Data RJ-45 (Ethernet) 4 PIN Interlock (Vin) USB Micro-AB SIM Nano (4FF) 1.8 / 3.0V
USB	USB 2.0 USB Tethering	Environmental	Operating Temperature -40°C to +85°C -40°F to +185°F Humidity 5-95%, non-condensing
SMS	SMS to/from Ethernet via Telnet SMS Alerts SMS Remote Reboots	Weight	~105 grams
Carrier Connection	ICMP Keep Alive, DDNS	Dimensions	~1.75" x 1.75" x 1.35" (45mm x 45mm x 35mm)
GPS	TCP Server, UDP/Email Reporting, GpsGate	Approvals	FCC/IC PTCRB CE EN301908-1, EN301908-2, EN301908-13 EN303413, EN301489-1, EN301489-52 EN 62311, EN55032, EN55035, EN62368 RCM: Australia & New Zealand RoHS Compliant
Navigation Update Rate Accuracy	Up to 5 Hz Position: 2.5 m CEP SBAS: 2.0 m CEP	Order Options	
Acquisition	Cold Starts: 27 seconds Aided Started: 4 seconds Hot Starts: 1 seconds		
Sensitivity (Active/Passive Antenna)	Tracking : -159 dBm Cold Starts: -147 dBm Hot Starts: -156 dBm		
Network Protocols	IPv4, IPv6, TCP, UDP, TCP/IP, ARP, ICMP, DHCP, HTTP, SNMP, FTP, DNS, Modbus Slave (TCP), MQTT		
Security	VPN, IPSec(IKEv1/IKEv2//ISAKMP); Multiple tunnel support (16); 3DES and up to 256-bit AES Encryption, Site to Site Tunneling, L2TP, Open VPN), GRE, HTTPS, RADIUS		
Firewall	NAT, NAT-T VPN tunneling, Port forwarding, VPN/GRE pass-through; Access control lists (IP/MAC filtering), Data origin / integrity Authentication, DMZ	CA-MHK119420 LTECube-CAT4GL MHK119422 LTECube-CAT4GL w/Acc Kit	
Management	Telnet, WebUI, SNMP V1/2/3, Wireless Upgrade (HTTP/FTP), RADIUS authentication, AT Command Interface (Telnet), Microhard NMS Support, LWM2M, Data Usage Alerts, SSH		

Contact Information

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762

Copyright 2026 Microhard Systems Inc.
Specifications subject to change without notice.

