


Femto Hexa-Band Digital Data Link

The fDDL1624-SWP is a compact, enclosed, high power, Hexa-Band wireless solution that delivers the throughput and range needed for complex data intensive applications. The fDDL1624-SWP offers software selectable operation in six frequency bands between 1.6 and 2.5 GHz. The fDDL1624-SWP uses Maximal Ratio Combining (MRC), Maximal Likelihood (ML) decoding and Low-Density Parity Check (LDPC) to achieve robust RF performance. The fDDL1624-SWP features secure and simultaneous Ethernet and Serial Data Communications.



Up to 21 Mbps

Hexa-Band Frequency

Ethernet & Serial

Dynamic Frequency Selection

PTP | PMP | Relay | MESH

MANET MESH / Advanced MESH

Real Time Spectrum Analyzer

New Dynamic Frequency Selection on OFDM overlay provides robust interference and antijam immunity!

Features

- Software Selectable 1.6, 1.8, 2.0, 2.2, 2.3 or 2.4 GHz Operation
- Maximal Ratio Combining (MRC), Maximal Likelihood (ML) decoding
- Low-Density Parity Check (LDPC)
- Up to 21 Mbps Iperf Throughput @ 8 MHz channel (-78 dB)
 - Up to 2 Mbps IPerf Throughput @ 4 MHz channel (-100 dB)
- Serial Data/Console Communication Ports
- Dual 10/100 Ethernet Ports (LAN/WAN)
- Point-to-Point, Point-to-Multipoint & MANET MESH Networks
- Master, Remote, Relay & MESH Operating Modes
- Adjustable total transmit power (up to 1W)
- FIPS140-2 Compliant Pending
- NDAA Section 889 Compliant



Optimal Performance Specifications					
Modulation	8MHZ Channel		4MHZ Channel		Total Tx Power +/- 1dB
	IPerf Throughput (Mbps)	Optimal MRC Sensitivity* (dB)	IPerf Throughput (Mbps)	Optimal MRC Sensitivity* (dB)	
Frequency Band: 1625 - 1725 MHz					
BPSK_1/2	3.1	-96.5	1.57	-100	30dBm
QPSK_1/2	6.0	-95	3.0	-98	30dBm
QPSK_3/4	8.4	-93	4.3	-96	30dBm
16QAM_1/2	10.7	-89	5.4	-92.5	30dBm
16QAM_3/4	14.8	-87	7.4	-90	30dBm
64QAM_2/3	18.1	-82	7.8	-85	30dBm
64QAM_3/4	19.0	-80.5	8.0	-83	30dBm
64QAM_5/6	21.0	-78	10.0	-80.5	30dBm
Frequency Band: 1780 - 1850 MHz					
BPSK_1/2	3.1	-96.5	1.57	-100	30dBm
QPSK_1/2	6.0	-95	3.0	-98	30dBm
QPSK_3/4	8.4	-93	4.3	-96	30dBm
16QAM_1/2	10.7	-89	5.4	-92.5	30dBm
16QAM_3/4	14.8	-87	7.4	-90	30dBm
64QAM_2/3	18.1	-82	7.8	-85	30dBm
64QAM_3/4	19.0	-80.5	8.0	-83	30dBm
64QAM_5/6	21.0	-78	10.0	-80.5	30dBm
Frequency Band: 2020 - 2110 MHz					
BPSK_1/2	3.1	-96.5	1.57	-100	30dBm
QPSK_1/2	6.0	-95	3.0	-98	30dBm
QPSK_3/4	8.4	-93	4.3	-96	30dBm
16QAM_1/2	10.7	-89	5.4	-92.5	30dBm
16QAM_3/4	14.8	-87	7.4	-90	30dBm
64QAM_2/3	18.1	-82	7.8	-85	28dBm
64QAM_3/4	19.0	-80.5	8.0	-83	28dBm
64QAM_5/6	21.0	-78	10.0	-80.5	27dBm
Frequency Band: 2200 - 2300 MHz					
BPSK_1/2	3.1	-96.5	1.57	-100	30dBm
QPSK_1/2	6.0	-95	3.0	-98	30dBm
QPSK_3/4	8.4	-93	4.3	-96	30dBm
16QAM_1/2	10.7	-89	5.4	-92.5	28dBm
16QAM_3/4	14.8	-87	7.4	-90	28dBm
64QAM_2/3	18.1	-82	7.8	-85	28dBm
64QAM_3/4	19.0	-80.5	8.0	-83	28dBm
64QAM_5/6	21.0	-78	10.0	-80.5	27dBm
Frequency Band: 2300 - 2390 MHz					
BPSK_1/2	3.1	-96.5	1.57	-100	30dBm
QPSK_1/2	6.0	-95	3.0	-98	30dBm
QPSK_3/4	8.4	-93	4.3	-96	30dBm
16QAM_1/2	10.7	-89	5.4	-92.5	28dBm
16QAM_3/4	14.8	-87	7.4	-90	28dBm
64QAM_2/3	18.1	-82	7.8	-85	28dBm
64QAM_3/4	19.0	-80.5	8.0	-83	28dBm
64QAM_5/6	21.0	-78	10.0	-80.5	27dBm
Frequency Band: 2400 - 2500 MHz					
BPSK_1/2	3.1	-96.5	1.57	-100	30dBm
QPSK_1/2	6.0	-95	3.0	-98	30dBm
QPSK_3/4	8.4	-93	4.3	-96	30dBm
16QAM_1/2	10.7	-89	5.4	-92.5	28dBm
16QAM_3/4	14.8	-87	7.4	-90	28dBm
64QAM_2/3	18.1	-82	7.8	-85	28dBm
64QAM_3/4	19.0	-80.5	8.0	-83	28dBm
64QAM_5/6	21.0	-78	10.0	-80.5	27dBm

*RX Sensitivity +/- 1.5 dB. Bands starting at 2280 MHz and higher, subtract 1.5~3 dB.

fDDL1624-SWP Specifications



Frequency (Software Selectable)	1625 to 1725 MHz 1780 to 1850 MHz 2020 to 2110 MHz 2200 to 2300 MHz 2300 to 2390 MHz 2400 to 2500 MHz
Error Detection	32 bits of CRC, ARQ
Encryption (Requires Export Permit)	256-bit AES
Ports Serial Data/Console Ethernet USB	RS232 (300bps to 921kbps) Dual 10/100 IEEE802.3 (LAN/WAN) 2.0
Firewall	Port Forwarding, Access Control, IP/MAC List.
Operating Modes	Point-to-Point, Point-to-Multipoint, Repeater, MANET Mesh
Diagnostics	Remote Diagnostics, Ping, Traceroute, ARP table, DHCP active leases, IPPerf, RSSI
Management	Local Serial Port Console, Telnet, WebUI, SNMP, FTP Upgrade, TFTP, AT Command Interface
Rejection	Excellent strong signal interference & rejection characteristics
Input Voltage	7-30 V _{DC}
Mating Connector	Power, Data: 10-Pin (GHR-10V-S) Antenna: MMCX
Environmental Temperature Humidity	-40°F to 185°F (-40°C to +85°C) 5-95%, non-condensing

Weight	~32 grams
Dimensions	~30 x 40 x 18 mm
Approvals/Compliance	NDAA Section 889 Compliant FIPS140-2 Compliant Pending

Order Options

Model	Part Number	Description
fDDL1624-SWP	MHK185360	fDDL1624 FEMTO Hexa-Band ENC Digital Data Link

Microhard Confidential

Preliminary



Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

www.microhardcorp.com
 info@microhardcorp.com
 1-855-353-0028